

T22Q03267

Fire Retardant Linen Canvas



| CHARACTERISTICS | |
|---------------------|----------------------|
| COMPOSITION | 100% Linen |
| WEIGHT | 636 g/m ² |
| USABLE WIDTH | 140 |
| ORIGIN | Italy |
| DYEING PROCESS | Piece Dyed |
| FIRE RESISTANT (FR) | Yes |

| RECOMMENDED CARE: |
|---|
| Wash at 30° gentle cycle - Do not tumble dry - Iron at low temperature - (F) Professional cleaning with hydrocarbon solvents only - Do not bleach |

| COMPLIANCE & TRACEABILITY |
|---|
| This material selected by a prestigious Couture House, is certified "deadstock" from the LVMH group. It originally comes from an internationally-renowned manufacturer and is produced in compliance with REACH Regulation - UE 1907/2006 and LVMH RSL (Restricted substances List) |

QUALITY CONTROL

| | | |
|----------|-------------|-----------------------------------|
| ABRASION | 25.000 runs | Martindale- UNI EN ISO 12947-2/00 |
| PILLING | 3/4 | Martindale- UNI EN ISO 12945-2/02 |

| | Warp | Weft | Norme |
|----------------------------------|---------|--------|--------------------------------------|
| SHRINKAGE (Hoffmann press) | -2 | -2 | DIN 53894-2 - modif. ciclo continuo) |
| SHRINKAGE (Dry cleaning) | -2 | -2 | UNI EN ISO 3175-2/01 |
| SHRINKAGE (Domestic cleaning) | -3/4 | -3/4 | UNI EN ISO 6330:12 |
| SEAM SPLIPPAGE | 3,08 mm | 4,8 mm | UNI EN ISO 13936-2/04 |

COLORFASTNESS

| | | |
|-------------|---|-----------------------|
| LIGHT | 5 | UNI EN ISO 105 B02/04 |
| DRY RUBBING | 4 | UNI EN ISO 105 X12/03 |
| WET RUBBING | 3 | UNI EN ISO 105 X12/03 |



Paris Trade and Companies Register under number 842 426 769

Nona Source – 12 rue Philippe de Girard – 75010 Paris – France

VAT Number: FR27842426769

contact@nona-source.com